



SPECIFICATIONS		DESCRIPTION		REMARKS
Model	CB6	1. BODY	1set	1. OPTION : Top Jaw & Locator
Jaw Stroke(Dia.)	8.7 mm			2. CB6 chuck equipped two holes for air & coolant is available as option.
Plunger Stroke	12 mm			
Chucking Range(Max.)	120 mm			3. Adaptor for A-type spindle nose is available as option
Chucking Range(Min.)	12 mm			
Max. Input	21.2 kN			4. Re-assemble of master jaw is required ID chucking.
Max. Stafic Gripping Force	59.4 kN			
Max. Speed	4,000 min⁻¹			
GD²	0.22kgf·m²			
Net Weight	14 kg			

NOTE		HEAT TREATMENT	MODEL: CB6
3RD ANGLE PROJECTION	S5	MATERIAL	DRAWING No.
APPROVED / CHECKED / DESIGNER		QUANTITY / SCALE 1:1 / DATE	PART NAME
FUJI MACHINE MFG.CO.,LTD. 富士機械製造株式会社 A1			TITLE: Ball-Lok Chuck / USER

MACHINING TOLERANCE (mm): DIMENSIONS 0.5≤X≤3, 3<X≤6, 6<X≤30 | SURFACE TOLERANCE: ±0.1, ±0.2, ±0.3 | I.D./O.D. TOLERANCE: ±0.05, ±0.1, ±0.2 | DIMENSIONS: 30<X≤120, 120<X≤315, 315<X≤1200 | SURFACE TOLERANCE: ±0.3, ±0.5, ±0.8 | I.D./O.D. TOLERANCE: ±0.15, ±0.2, ±0.3 | HOLE PITCH: HOLE AND REFERENCE THROUGH HOLE DISTANCE FROM TARGET POINT UP TO 0.4mm DISPLACEMENT TOLERANCE FOR ALL HOLE CENTER WITHIN 0.5mm PER 50mm | ENVELOPE PARALLELISM | PARALLELISM | PERPENDICULARITY | CONCENTRICITY | RUNOUT