

NXTR Specifications

| Module | | 1R module | 2R module | |
|--------------------------|-----------------|---|--------------------------|-------------------------|
| Panel size (L x W) | Single conveyor | 48 x 48 to 750 x 610 mm | 48 x 48 to 370 x 610 mm | |
| | Double conveyor | Single conveyance | 48 x 48 to 370 x 510 mm | |
| | | Dual conveyance | 48 x 48 to 750 x 280 mm | 48 x 48 to 370 x 280 mm |
| Weight | | 755 kg | 865 kg | |
| Base | | One module base | Two module base | |
| Air consumption | | 60 L/min (ANR) | 132 L/min (ANR) | |
| Machine size (L x W x H) | | 795 x 1,740 x 1,480 mm | 1,590 x 1,740 x 1,480 mm | |
| Weight | | 540 kg | 1,080 kg | |
| Head | | RH20 | RH08 | RH02 |
| Throughput*1 | | 50,000 cph | 30,000 cph | 9,000 cph |
| Placing accuracy*1 | | ±0.025 mm Cpk ≥ 1.00 | | |
| Power | | 3-phase AC 200 to 230 V ±10V (50/60 Hz) | | |
| Air | | 0.4 MPa | | |
| Part supply unit | | Cassette-type feeder, Fuji Intelligent Feeder, Tray unit-RM | | |

*1 Under optimum Fuji conditions.

NXTR PM Specifications

| | | | |
|-------------------------------|-----------------|--|-------------------------|
| Repeated alignment accuracy*1 | | ±0.010 mm @6σ (Cpk ≥ 2.0) | |
| Printing accuracy*2 | | ±0.020 mm @6σ (Cpk ≥ 2.0) | |
| Printing speed | | 1 to 300 mm / sec. | |
| Panel size (L x W) | Single conveyor | 48 x 48 to 610 x 610 mm | |
| | Double conveyor | Single conveyance | 48 x 48 to 610 x 510 mm |
| | | Dual conveyance | 48 x 48 to 330 x 280 mm |
| Screen frame (L x W) | | 650 x 550 mm, 29 x 29 inch, 750 x 750 mm, 750 x 810 mm | |
| Machine size (L x W x H) | | 1,280 x 1,700 x 1,480 mm | |
| Weight | | 1,600 kg | |
| Power | | 3-phase AC 200 to 230 V ±10V (50/60 Hz) | |
| Air | | 0.4 MPa | |
| Air consumption | Single conveyor | 7.7 L/min (ANR) | |
| | Double conveyor | 37.0 L/min (ANR) | |

*1 Under optimum Fuji conditions.

*2 Under optimum Fuji conditions. (Using CeTaQ's measurement system)